

DMUA-FA ECONOMY MAKE-UP AIR

CAPTIVEAIR
COMMERCIAL VENTILATION EQUIPMENT



- Air Volume: 350 - 2460 cfm
- Maximum SP: 0.5" wg. @ standard air density

Can be used anywhere fresh air is needed to replace exhaust air, commercial kitchens, office buildings, bakeries, laundries, factories, warehouses, foundries, locker rooms, etc.

FEATURES & BENEFITS

- Emergency disconnect switch.
- Spun aluminum housing for rust free weather resistant durability.
- Propellers constructed with die formed blades riveted to a steel hub.
- Can be roof or wall mounted.
- Standard bird screen.
- Wire conduit to provide a clear channel for electrical connections.

OPTIONS

- Motorized Damper.
- Wall Mount Sleeve.
- Roof Curb.

CERTIFICATIONS

The DMUA-FA Model has been certified by ITS. This certification mark indicates that the product has been tested to and has met the minimum requirements of a widely recognized (consensus) U.S. products safety standard, that the manufacturing site has been audited, and that the applicant has agreed to a program of periodic factory follow-up inspections to verify continued performance.



Model DMUA-FA is ETL Listed under file number 3049729-002 and complies with UL705 and CSA C22.2, No. 113 Standards.