

SIDE MOUNT UNDERCOUNTER FREEZERS

100% FRONT BREATHING SYSTEM



JUF-36



JUF-48



JUF-60

≡ FEATURES & BENEFITS ≡

■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ SIDE MOUNT COMPRESSOR UNIT

Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a **front breathing** feature, this model can provide high efficiency in narrow spaces.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

■ EXTERIOR & INTERIOR OF THE CABINET

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES

■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ FREEZER HOLDS -5°F ~ -10°F FOR THE BEST IN FROZEN FOOD PRESERVATION

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D* x H† (inches)
JUF-36	1	7	1	1/3	5.0	176	35 ³ / ₈ x 27 ¹ / ₂ x 28 ³ / ₄
JUF-48	2	11	2	1/3	5.0	205	47 ¹ / ₄ x 27 ¹ / ₂ x 28 ³ / ₄
JUF-60	2	15	2	1/3	5.5	240	59 x 27 ¹ / ₂ x 28 ³ / ₄

*Depth does not include 1" for rear spacers. † Height does not include 5-7/8" for caster height.

JUF MODELS SPECIFICATIONS

ELECTRICAL DATA	JUF-36	JUF-48	JUF-60
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	Ⓜ NEMA-5-15P	Ⓜ NEMA-5-15P	Ⓜ NEMA-5-15P
Full Load Amperes	5.0	5.0	5.5
Compressor HP	1/3	1/3	1/3
Cord Length ft.	9.2	9.2	9.2
Refrigerant	R-404A	R-404A	R-404A
DIMENSIONAL DATA			
Net Capacity cu. ft.	7	11	15
Ext. Length Overall in.	35 ³ / ₈ (899mm)	47 ¹ / ₄ (1200mm)	59 (1499mm)
Ext. Depth Overall in.*	27 ¹ / ₂ (699mm)	27 ¹ / ₂ (699mm)	27 ¹ / ₂ (699mm)
Ext. Height Overall in.†	28 ³ / ₄ (730mm)	28 ³ / ₄ (730mm)	28 ³ / ₄ (730mm)
# of Doors	1	2	2
# of Shelves	1	2	2
Gross Weight lbs.	176	205	240
Net Weight lbs.	157	184	205


Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

*Depth does not include 1" for rear spacers. † Height does not include 5-7/8" for caster height.

■ **WARRANTY : 1 Year Parts and Labor Warranty**
Additional 4 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM
- 4" DIAMETER CASTERS ARE STANDARD
- 2.5" DIA. CASTERS AVAILABLE (OPTIONAL)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)



PLAN VIEW