Model:

CFD-Series:

CFD-1RR

Reach-In Solid Swing Door Refrigerator



CFD-1RR

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
 Heavy-duty pull handle
 Each door with two spring hinges, this
 make the door self-closing with with
 enduring quality
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP.				
			L	D	Н	LITER H	HP	Voltage	Amps	NEMA Config.
CFD-1RR	1	3	29 736	32.2 818	82.5 2095	23 650	1/4+	115/60/1	7.4	5-15P (i)

Plug type varies by country.





