Model:

CFD-Series:

CFD-3FF

Reach-In Solid Swing Door Freezer



CFD-3FF

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
 Heavy-duty pull handle
 Each door with two spring hinges, this make the door self-closing with with enduring quality
- Refrigeration system holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

| | | | Cabinet Dimensions (inches / mm) | | | CAP. CU.FT. | A 32 - 1 | | | NEMA Config. |
|---------|-------|---------|-------------------------------------|-------------|--------------|----------------|----------|----------|------|--|
| Model | Doors | Shelves | L | D | Н | LITER | HP | Voltage | Amps | 5-20P |
| CFD-3FF | 3 | 9 | 80.9 2054 | 32.2 818 | 82.5 2095 | 72 2040 | 1 | 115/60/1 | 14 | 30 amps Circuit Breaker is recommended to be connected to the plug base directly |

Plug type varies by country.





