

PO Box 5932, Spartanburg, SC 29304 1-888-845-9800 Fax# 1-864-582-5083 http://www.Beverage-Air.com

# **Commercial Refrigeration Equipment General Specification**

## WTR AND WTF—SERIES WORKTOP UNITS

Select from 4 standard sizes in widths of 46" (1 door), 67" (2 door), 93" (3 door), and 119" (4 door). Working height\* is 35 1/2" with units installed on 6 inch casters (2 with brakes).

### CABINET CONSTRUCTION

Heavy duty construction includes stainless steel on front, sides, door(s) and grille. Worktop is stainless steel with built-in backsplash. Cabinet back and bottom are galvanized steel. Interior liner is made of anodized aluminum for longer lasting corrosion protection. Interior thermometer is standard.

Cabinets are insulated with foamed-in-place polyurethane insulation of 2" minimum thickness. Work tops are 2 1/2". Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Door openings include low wattage, anti-condensate heaters. A plug-in type vinyl magnetic gasket is attached to each door for positive seal. Convenient, contoured, pull handle is made of black anodized aluminum. Interior arrangement includes 2 steel wire epoxy coated shelves behind each door, adjustable in 1/2 inch increments.

# REFRIGERATION

Balanced refrigeration systems used in all 4 sizes of selfcontained refrigerated worktops provide high humidity storage of product at 35°F to 38°F. One size worktop freezer WTF67 holds product at 0°F and below. Unit is equipped with time activated, temperature terminated, electric defrosting, Refrigerants include CFC free R134a in refrigerators and 404A in freezers to comply with all environmental concerns.

## **ELECTRICAL**

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

### SPECIAL FEATURES


- Cartridge style door hinges provides positive seal & eliminates door sagging issues (excludes glass door and some special units).
- 6" casters, two with brakes standard.
- Optional 6" legs or 3" casters available

\*Note: Overall heights of casters may vary with different types of casters depending upon caster manufacturer designations.









**WORK TOP** REFRIGERATORS AND FREEZER WORKTOP FREEZER 32" BASE MODEL SERIES MODELS: WTR46A WTR67A WTR93A **WTR119A** WTF67A



**WTR46** 



#### WTR67/WTF67

## **ELECTRICAL CONNECTION**

Units pre-wired at factory and include 8' long cord and plug set.



Available From:

Model Specified	Store#
Location	Quantity



# Work Top Refrigerators and Freezer

#### Models: WTR46A, WTR67A, WTR93A, WTR119A, WTF67A WTR46A WTR67A WTR93A WTR119A WTF67A EXTERNAL DIMENSIONAL DATA Length Overall (inches) 67" 1702 1702 Length Overall (mm) 1168 2362 3023 Depth Overall (inches) - Less handle Depth Overall (mm) - Less handle 35 7/8 35 7/8 35 7/8 35 7/8 813 911 911 911 911 Height Overall— on 6" casters (inches)\* Height Overall—on 6" casters (mm)\* 37 1/4 39 1/2 39 5/8 37 3/8 39 1/2 LEFT SIDE VIEW WTR46A Depth with Door Open 90 ° 55 3/8" 55 7/8" 55 7/8" Clear Door Opening (inches) 21 1/2 21 1/2" x 21 1/2" x 21 1/2" x 23 1/2" 23 1/4" x 23 1/2" 25 1/4" 23 1/2" x 23 Number of doors 23 1/2" INTERNAL DIMENSIONAL DATA 765 NET Capacity (Liters) 100 1/8 Internal Length Overall (inches) Internal Length Overall (mm) 1219 1880 1219 LEFT SIDE VIEW Internal Depth Overall (inches) 26" 28" 28" 28" WTR67A 660 711 711 Internal Height Overall (inches) 23" 25" 24" 25 1/4" 25" Internal Height Overall (mm) 597 635 610 641 635 OVERALL DEPTH 24 3/8" DOOR WIDTH Number of shelves 2 4 6 8 4 **ELECTRICAL DATA** 29 1/2" 26 \$/8" 29 1/2" DOOR Full Load Amperes 115/60/1 6.3 8.6 8.6 8.6 **ENERGY CONSUMPTION (KWH)** 2.81 2.56 3.49 3.91 15.3 REFRIGERATION DATA Horsepower 1/4 1/4 1/3 1/3 3/4 WTR93A WEIGHT DATA LEFT SIDE VIEW Gross Weight (Crated lbs) 410 486 604 425 35 7/8" OVERALL DEPTH Gross Weight (Crated kg) 193 134 186 \*Note: Overall heights of casters may vary with different types of casters depending upon caster manufacturer designations.

# **PLAN VIEWS**

